




AudioSync | Technical Data

ITC R

In-The-Canal Rechargeable

Fitting Range

- L
- M
- P
- UP



Aris AI 24 | 20 | 16

Color Guide

Faceplate Colors



Shell Colors



Patient Features

- IP Rating: 68
- Tinnitus Technology
- Wireless Connectivity
- Rechargeable Battery

Aris AI Technology

- Personal health monitoring technology with embedded sensors and artificial intelligence
- Compatible with StarLink 2.0 accessories and StarLink Edge accessories

	L	M	P	UP	Matrices: L, M, P, UP Battery: Lithium-ion
Measurement	ANSI/IEC 2cc Coupler	ANSI/IEC 2cc Coupler	ANSI/IEC 2cc Coupler	ANSI/IEC 2cc Coupler	
Peak OSPL90 (dB SPL)	110	114	117	125	
HFA OSPL90 (dB SPL)	105	109	113	122	
Peak Gain (dB)	40	50	59	68	
HFA Full-On Gain (dB)	36	46	55	63	
Frequency Range (Hz)	<100-9600	<100-8400	<100-6600	<100-5300	
HFA Frequencies (kHz)	1.0,1.6,2.5	1.0,1.6,2.5	1.0,1.6,2.5	1.0,1.6,2.5	
Reference Test Gain (dB)	28	32	36	45	
Equivalent Input Noise (dB SPL) Expansion On (Default)	15	15	15	15	
Equivalent Input Noise (dB SPL) Expansion Off	25	25	25	25	
Harmonic Distortion					
500 Hz (%)	<3	<3	<3	<3	
800 Hz (%)	<3	<3	<3	<3	
1600 Hz (%)	<3	<3	<3	<3	
Estimated Lithium-ion Battery Life*					
Without streaming (hrs)	Up to 42	Up to 42	Up to 42	Up to 42	
With streaming (hrs)	Up to 36	Up to 36	Up to 36	Up to 36	
Battery Current (mA)	0.9	0.9	0.9	0.9	
Tinnitus Therapy Stimulus					
Max RMS Output (dB SPL)	87	87	87	87	
Weighted RMS Output Level (dB SPL)	87	87	87	87	
Max 1/3 Octave Output (dB SPL)	87	87	87	87	

*Results will vary based on wireless usage.

AudioSync, Aris, and StarLink are trademarks of Starkey Laboratories, Inc.





©2025 Starkey Laboratories, Inc. All Rights Reserved. 4/25 SPEC3100-00-EN-AD



ITC R

In-The-Canal Rechargeable

Aris AI 24 | 20 | 16



Latency (ms)	4.3
Attack Time (ms)	3
Release Time (ms)	60




AudioSync | Technical Data

ITC R

In-The-Canal Rechargeable

Fitting Range

UP-



Aris AI 24 | 20 | 16

Color Guide

Faceplate Colors



Shell Colors



Patient Features

- IP Rating: 68
- Tinnitus Technology
- Wireless Connectivity
- Rechargeable Battery

Aris AI Technology

- Personal health monitoring technology with embedded sensors and artificial intelligence
- Compatible with StarLink 2.0 accessories and StarLink Edge accessories

UP-

Matrices: UP-

Battery: Lithium-ion

Measurement

ANSI/IEC
2cc Coupler



Peak OSPL90 (dB SPL)	119
HFA OSPL90 (dB SPL)	115
Peak Gain (dB)	64
HFA Full-On Gain (dB)	58
Frequency Range (Hz)	<100-6500
HFA Frequencies (kHz)	1.0, 1.6, 2.5
Reference Test Gain (dB)	38
Equivalent Input Noise (dB SPL) <i>Expansion On (Default)</i>	15
Equivalent Input Noise (dB SPL) <i>Expansion Off</i>	25
Harmonic Distortion	
500 Hz (%)	<3
800 Hz (%)	<3
1600 Hz (%)	<3

Estimated Lithium-ion Battery Life*

Without streaming (hrs)	Up to 42
With streaming (hrs)	Up to 36
Battery Current (mA)	0.9

Tinnitus Therapy Stimulus

Max RMS Output (dB SPL)	87
Weighted RMS Output Level (dB SPL)	87
Max 1/3 Octave Output (dB SPL)	87



Latency (ms)	4.3
Attack Time (ms)	3
Release Time (ms)	60

*Results will vary based on wireless usage.

AudioSync, Aris, and StarLink are trademarks of Starkey Laboratories, Inc.

©2025 Starkey Laboratories, Inc. All Rights Reserved. 4/25 SPEC3100-00-EN-AD